## Claims

1. Recording method for recording the status of an artificially ventilated lung of a patient in accordance with a plurality of lung positions, the patient lying in a nursing bed and the position of the artificially ventilated lung is moveable by a position actuator, comprising the steps of:

a) moving the artificially ventilated lung by the position actuator to a defined lung position,

5

15

b) determining the status of the artificially ventilated lung, and

c) recording the status of the artificially ventilated lung in accordance with the defined

lung position.

- 20 2. Recording method according to claim 1, wherein the nursing bed is rotatable around its longitudinal axis and wherein the position actuator is a rmotor rotating the nursing bed around its longitudinal axis.
- 25 3. Recording method according to claim 1, wherein the position actuator comprises air cushions provided underneath the patient.
- 4. Recording method according to one of the claims 1 3,
  wherein the defined lung position is reached by a
  predetermined step size of the position actuator.
  - 5. Recording method according to one of the claims 1 3, wherein the defined lung position is reached in

accordance with a feed back signal of a position sensor measuring the actual lung position.

- 6. Recording method according to one of the claims 1 5, wherein the status of the artificially ventilated lung is a measure of a regional or a global information on lung morphology and/or lung function.
- 7. Recording method according to one of the claims 1 5,
  wherein the status of the artificially ventilated lung
  is a measure of the functionality with regard to the
  global gas exchange of the lung.
- 8. Recording method according to one of the claims 1 7,
  wherein the determined status of the artificially
  ventilated lung is recorded by a computer in
  accordance with the corresponding defined lung
  position.
- 9. Recording method according to one of the claims 1 8, wherein the steps a), b), and c) are repeated with a predetermined differential step size of the position actuator until the status of the artificially ventilated lung has been determined over a predetermined range of lung positions.
- 10. Controlling method for controlling at least one ventilation pressure of an artificial ventilator for ventilating an artificially ventilated lung of a patient in accordance with a plurality of lung positions, the patient lying in a nursing bed and the position of the artificially ventilated lung is moveable by a position actuator, comprising the steps of:

a) obtaining lung status information which is based on at least two supporting points of a first status of the artificially ventilated lung in accordance with a first lung position and a second status of the artificially ventilated lung in accordance with a second lung position,

- b) moving the artificially ventilated lung by the position actuator to a defined lung position,
- c) controlling of at least one ventilation pressure in accordance with the defined lung position and in accordance with the lung status information related to said defined lung position.

5

10

15

25

30

- 11. Controlling method according to claim 10, wherein the lung status information is obtained by applying the recording method according to claim 9.
- 20 12. Controlling method according to one of the claims 10 -11, wherein the lung status information is interpolated between the supporting points in accordance with the difference between two neighbouring supporting points.
  - 13. Controlling method according to one of the claims 10 12, wherein at least one ventilation pressure is controlled such that the lung status information yields a homogeneous distribution over a plurality of lung positions.
  - 14. Positioning method for controlling the change of the position of an artificially ventilated lung of a patient, the patient lying in a nursing bed and the position of the artificially ventilated lung is

changeable by a corresponding position actuator, comprising the steps of:

- a) providing a periodical controlling signal having a distribution of a plurality of position periods and/or of a plurality of amplitudes,
  - b) controlling the position actuator by said periodical controlling signal.

10

5

15. Positioning method according to claim 14, wherein the distribution is compiled via a user's interface on the basis of a given set of periodical controlling signals.

15

20

- 16. Positioning method according to claim 14, wherein the distribution is compiled in accordance with lung status information which is based on at least two supporting points of a first status of the artificially ventilated lung in accordance with a first lung position and a second status of the artificially ventilated lung in accordance with a
- 25 17. Recording apparatus for recording the status of an artificially ventilated lung of a patient lying in a nursing bed in accordance with a plurality of lung positions, comprising:

second lung position.

- a) a position actuator for moving the artificially ventilated lung to a defined lung position,
  - b) determining means for determining the status of the artificially ventilated lung, and

- c) recording means for recording the status of the artificially ventilated lung in accordance with the defined lung position.
- 18. Recording apparatus according to claim 17, wherein the nursing bed is rotatable around its longitudinal axis and wherein the position actuator is a motor rotating the nursing bed around its longitudinal axis.
- 10 19. Recording apparatus according to claim 17, wherein the position actuator comprises air cushions provided underneath the patient.
- 20. Recording apparatus according to one of the claims 17
  15 19, wherein the defined lung position is reached by a predetermined step size of the position actuator.
- 21. Recording apparatus according to one of the claims 17
   19, wherein the defined lung position is reached in
  accordance with a feed back signal of a position
  sensor measuring the actual lung position.
  - Recording apparatus according to one of the claims 17
     21, wherein the status of the artificially ventilated lung is a measure of a regional or a global information on lung morphology and/or lung function.

25

- 23. Recording apparatus according to one of the claims 17 21, wherein the status of the artificially ventilated lung is a measure of the functionality with regard to the global gas exchange of the lung.
  - 24. Recording apparatus according to one of the claims 1723, wherein the determined status of the artificially ventilated lung is recorded by a computer

in accordance with the corresponding defined lung position.

25. Recording apparatus according to one of the claims 17
5 - 24, wherein a predetermined differential step size is applied repeatingly to the position actuator until the status of the artificially ventilated lung has been determined over a predetermined range of lung positions.

10

15

20

30

26. Controlling apparatus for controlling at least one ventilation pressure of an artificial ventilator for ventilating an artificially ventilated lung of a patient lying in a nursing bed in accordance with a plurality of lung positions, comprising:

a) means for obtaining lung status information which is based on at least two supporting points of a first status of the artificially ventilated lung in accordance with a first lung position and a second status of the artificially ventilated lung in accordance with a second lung position,

- b) a position actuator for moving the artificially ventilated lung to a defined lung position,
  - c) means for controlling of at least one ventilation pressure in accordance with the defined lung position and in accordance with the lung status information related to said defined lung position.
- 27. Controlling apparatus according to claim 26, wherein the lung status information is obtained by using the recording apparatus according to claim 25.

28. Controlling apparatus according to one of the claims 26 - 27, wherein the lung status information is interpolated between the supporting points in accordance with the difference between two neighbouring supporting points.

- 29. Controlling apparatus according to one of the claims 26 28, wherein at least one ventilation pressure is controlled such that the lung status information yields a homogeneous distribution over a plurality of lung positions.
- 30. Positioning apparatus for controlling the change of
  the position of an artificially ventilated lung of a
  patient lying in a nursing bed, comprising:
  - a) a position actuator for changing the position of the artificially ventilated lung,

20 .

5

10

b) means for providing a periodical controlling signal having a distribution of a plurality of position periods and/or of a plurality of amplitudes, and

- c) means for controlling the position actuator by said periodical controlling signal.
- 31. Positioning apparatus according to claim 30, wherein
  the distribution is compiled via a user's interface on
  the basis of a given set of periodical controlling
  signals.
- 32. Positioning apparatus according to claim 30, wherein the distribution is compiled in accordance with lung

status information which is based on at least two supporting points of a first status of the artificially ventilated lung in accordance with a first lung position and a second status of the artificially ventilated lung in accordance with a second lung position.